

WESTERN RUBBER & SUPPLY, INC

6161 INDUSTRIAL WAY

LIVERMORE CA 94551

PH 925-960-8700

FX 925-960-8720

WWW.WESTERNRUBBER.COM

SALES@WESTERNRUBBER.COM

“GRADE 2100”

COMMERCIAL GRADE

50 Shore “A”

DESCRIPTION:

Commercial Grade silicone sheeting is designed to be used in applications where physical properties are not critical but extreme temperature resistance is still needed. Material is available in 30-80 durometer in many colors. Sheet thickness ranges from 1/64” up to 1” thick. Available width is up to 60” wide. Call customer service for many other variations of this material..

FEATURES:

- Excellent Gasketing Material
- Extreme High & Low Temperature Resistant
- UV / Ozone Resistant
- Non- Toxic, Chemically Inert
- Fungus Resistant

PHYSICAL PROPERTIES

PROPERTIES	Test Method	Typical Properties
Specific Gravity, G/CC	ASTM D297	1.45
Durometer, Shore “A”	ASTM D2240	50 +/-5
Tensile Strength, psi	ASTM D412	600
Elongation, %	ASTM D412	300
Tear, psi Die “B”	ASTM D624	80
Temperature Range	(°F)	-103 to +450 (+500 Intermittent)

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.