

WESTERN RUBBER & SUPPLY, INC.

6161 INDUSTRIAL WAY

LIVERMORE CA 94551

PH 925-960-8700

FX 925-960-8720

WWW.WESTERNRUBBER.COM
SALES@WESTERNRUBBER.COM

Other Data Sheets Are Available On Our Website

“GRADE 2400” SPECIFICATION GRADE SILICONE SHEET 50 Shore “A”

DESCRIPTION:

Specification Grade silicone sheeting is designed to be used in applications where higher physical properties are required. The material is available in continuous rolls or sheets. It is resistant to extreme high and low temperatures, and is proven to be an excellent gasketing material. Available in many colors. Red and grey are standard. Sheet thickness ranges from 1/64” up to 1” thick. Available width is up to 60” wide. Call customer service for many other variations of this material.

FEATURES:

- Excellent Gasketing Material
- Extreme High & Low Temperature Resistant
- UV / Ozone Resistant
- Non- Toxic, Chemically Inert
- All FDA approved Ingredients
- Low Compression Set
- Fungus Resistant

SPECIFICATIONS:

ZZR-765 CL2A & 2B GR50
AMS3302
ASTM D2000

PHYSICAL PROPERTIES

PROPERTIES	Test Method	Typical Properties
Specific Gravity, G/CC	ASTM D297	1.45
Durometer, Shore “A”	ASTM D2240	50 +/-5
Tensile Strength, psi	ASTM D412	850
Elongation, %	ASTM D412	400
Tear, psi Die “B”	ASTM D624	120
Temperature Range	(°F)	-103 to +500

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.