

WESTERN RUBBER & SUPPLY, INC

6161 INDUSTRIAL WAY

LIVERMORE CA 94551

PH 925-960-8700

FX 925-960-8720

WWW.WESTERNRUBBER.COM

SALES@WESTERNRUBBER.COM

Closed Cell Silicone Sponge

MEDIUM FLAME RETARDANT

DESCRIPTION:

Flame retardant Silicone sponge is an excellent material for gasketing applications that require a soft compressible material. It is resistant to extreme temperatures. It comes in a dark blue/grey color. The surface has a fine fabric finish on both sides and is available in continuous rolls up to 1/2" thick.

FEATURES:

- Flame Retardant
- High Compressibility
- Low Compression Set
- UV / Ozone Resistant
- Excellent Gasketing Material

SPECIFICATIONS:

Capable of Meeting:

DMS1980

UL 94 HB

Properties	Test Method	Typical Values
Density, lbs/cubic in. Under 1/4" thick	(ASTM D-297)	.020
Density, lbs/cubic in. Over 1/4" thick	(ASTM D-297)	.018
Compression Deflection, PSI	(ASTM D-1056)	6-14
Compression Set	(ASTM D-1056)	15
Brittle Point °F		-103
Temperature Range °F		-103 to +450
Water Absorption	(ASTM D-1056)	Pass
Tensile Strength, PSI	(ASTM D-412)	90
Elongation, %	(ASTM D-412)	150

The above values are typical properties and are provided for information only. They should not be used to set specification requirements. It is up to the end user to determine whether the material is suitable for the intended application.